

Terra Shield®

We make a material difference

Outerwrap and Rockshield



Tapecoat®

Technical Data Sheet

DESCRIPTION

Tapecoat Terra Shield® a 0.4" thick, tough, resilient, perforated protective membrane applied over the pipeline coating to protect the integrity of the coating from damage or abrasion from handling, backfill and soil stress. Terra Shield protects the pipe coating by isolating and cushioning the pipe from abrasives, rock, debris and destructive backfill while allowing the cathodic protection system to maintain an uninhibited current flow. Terra Shield is made up of a 3/8" closed cell polyethylene foam with ½"

perforations 1 ¼" on center to enhance the function and free flow of the cathodic protection system. A 25 mil heavy duty polyethylene outside layer is heat fused to the Terra Shield® foam base providing even greater mechanical

strength.

SUBSTRATE COMPATIBILITY

Any protective coating in need of additional mechanical protection

RECOMMENDED USE

Ideal for protecting coatings in high soil stress areas or in the presence of

rocky, abrasive backfill.

SURFACE PREPARATION

None Required. Terra Shield is a mechanical protective overwrap, not a

corrosion preventative coating.

SAFETY

Refer to Material Safety Data Sheet: MSDS-Terra-Shield

APPLICATION

Refer to Application Guidelines: AG-COLD-APPLIED-ELASTOMERIC-TAPE, AG-

COLD-APPLIED-ELASTOMERIC-TAPE

TYPICAL DATA

Property	US Customary	Metric
Color	Black	Black
PE Outer Layer Thickness	25 mil	0.64 mm
Foam Thickness	3/8"	9.53 mm
Service Temperature Range	-40°F to 250°F	-40°C to 121°C

ORDERING INFORMATION

Roll Size	Coverage per Roll	Weight
5' x 140'	7 SQ (700 ft ²)	120# per Roll

Chase Corporation An ISO 9001:2008 REGISTERED COMPANY

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.

Liberty Sales & Distribution, LLC

2880 Bergey Road, Suite F, Hatfield, PA 19440 Phone: (877) 373-0118 Fax: (888) 850-3787 Email: sales@libertysales.net Web: www.libertysales.net

TDS-Terra-Shield-REV1-Aug13